



WINNER

PASSIVE FIRE PROTECTION
INNOVATION OF THE YEAR

DATASHEET | SMOKE CONTROL DAMPER

DEFENDER F2 EI 60S

PRODUCT DESCRIPTION

The Colt Defender F2 EI60S is a fire rated smoke control damper that controls the movement of smoke through a building. It forms part of a smoke ventilation system.

FEATURES & BENEFITS

- *Unique design creates a flush finish with the wall when closed, making it extremely discreet when installed*
- *External surfaces can be painted to match surrounding walls*
- *Constructed from mild steel and fire rated A1 noncombustible calcium silicate board*
- *Mineral wool insulation*
- *Advanced, multi-stage sealing system ensures smoke leakage is controlled in both ambient and fire conditions*
- *Fire rated to provide 60 minutes of integrity and insulation when closed*
- *Tested to EN 1363-1 and BS EN 1366 Parts 2 and 10*
- *Motor release from the corridor/lobby side for ease of maintenance.*



Description

The Colt Defender F2 has been specifically designed for use within mechanical shaft ventilation applications. This discreet fire rated smoke control damper is ideally suited to the Colt Shaft system, and can be controlled as part of the shaft system network.

Dimensions:

Aperture size 564mm x 1,151mm. Overall dimensions, including perforated bead edge to allow plaster finish right up to aperture edge, 740mm x 1,325mm.

Colour finishes/options:

Standard finish is white RAL 9010 matt, satin or gloss. Other colours are available on request.

Maintenance:

The Colt Defender F2 has been designed for ease of installation and maintenance without having to gain access to the shaft.

Design:

The unique design of the Defender F2 allows it to be as unobtrusive as possible and blend in with the surroundings. External surfaces can be treated with conventional interior paint to match surrounding walls.



Invisible Smoke Control



Unobtrusive when closed.



Effective ventilation when open.



Easy installation.



A bead edge profile is fixed to align with the opening edge to allow a plaster finish to be skimmed up to the opening.

Test results of the test specimens



Skimmed finish and damper panel can then both be painted to match.



Plaster and site paint finish in any standard interior wall paint or emulsion.

KEY FEATURES

Certified to EN 12101 Part 8 and is classified to EN 13501-4

*EI60 (Ved i<->o) S 1000
C300 AA Multi*

*Fire Integrity = 60 minutes
in both directions*

*Insulation = 60 minutes in
both directions*

*Suitable for installation in
vertical ducts or shafts*

Smoke sealed

Tested under pressure = 1000Pa

*Tested for 300 cycles – suitable
for testing once a month
for 25 years*

*Suitable for Automatic
Activation*

Multi compartment

*Suitable for applications
covered by ADB/9999/9991/
SCA Guide*

CE Marked

Classification to EN13501-4							
Integrity (min)	Insulation (min)	Smoke sealing (min)	Test pressure (Pa)	Direction of testing	Orientation of installation	Opening type	Activation method Automatic/Manual
61	61	61	1000	i <-> o	Ved	C300	AA

